

Model Gomtex

File Number: EX15216

COMPANY

PRODUCTOS Y MANGUERAS ESPECIALES S A

Pol Ind San Lazaro

Silo A10

S Domingo La Calzada, 26250 Spain

MODEL INFO

Gomtex

Single-jacketed covered

HOSE INFORMATION

Hose Size, in. (mm)	Service Test Pressure, psig (kPa)	Ratings	Comments	Heat Resistance Type
1-1/2 (38)	300 (2070)	Ozone resistant	Nitrile/PVC blend rubber lining, woven reinforcement of polyester, a nitrile/PVC blend rubber cover	--
1-3/4 (45)	250 (1725)	Ozone resistant	Nitrile/PVC blend rubber lining, woven reinforcement of polyester, a nitrile/PVC blend rubber cover	--
2-1/2 (65)	250 (1725)	Ozone resistant	Nitrile/PVC blend rubber lining, woven reinforcement of polyester, a nitrile/PVC blend rubber cover	--
3 (76)	250 (1725)	Ozone resistant	Nitrile/PVC blend rubber lining, woven reinforcement of polyester, a nitrile/PVC blend rubber cover	--
4 (102)	200 (1380)	Ozone resistant	Nitrile/PVC blend rubber lining, woven reinforcement of polyester, a nitrile/PVC blend rubber cover	--
5 (127)	200 (1380)	Ozone resistant	Nitrile/PVC blend rubber lining, woven reinforcement of polyester, a nitrile/PVC blend rubber cover	--

CONDUCTIVE HEAT EXPOSURE: STEEL BLOCK AT 400°C (752°F)

Hose Size, in. (mm)	Exposure Duration	Avg Leakage Rate @ 150 psi	Max Leakage Rate @ 150 psi
1-1/2 (38)	> 15 min	No Leakage	No Leakage
1-3/4 (45)	> 15 min	No Leakage	No Leakage
2-1/2 (65)	> 15 min	No Leakage	No Leakage
3 (76)	> 15 min	No Leakage	No Leakage

RADIANT HEAT EXPOSURE: 30 KW/M2

Hose Size, in. (mm)	Color/Marking	Exposure Duration	Avg Leakage Rate @ 150psi	Max Leakage Rate @ 150 psi
1-1/2 (38)	Red, no stripe	2 min 34 sec	1 gpm	1 gpm
1-3/4 (45)	Red, no stripe	2 min 25 sec	1 gpm	1 gpm
2-1/2 (65)	Red, no stripe	1 min 22 sec	1 gpm	1 gpm
3 (76)	Red, no stripe	1 min 15 sec	> 20 gpm	> 20 gpm

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."